

Pinhole exposure compensation time -Table 1

meter setting: f 16

Metered time:	1/250	1/125	1/60	1/30	1/15
Aperture	0.004	0.008	0.016667	0.033333	0.066667
100	0.2	0.3	0.7	1	3
125	0.2	0.5	1	2	4
150	0.4	0.7	1	3	6
175	0.5	1.0	2	4	8
200	0.6	1	3	5	10
225	0.8	2	3	7	13
250	1	2	4	8	16
275	1	2	5	10	20
300	1	3	6	12	23
325	2	3	7	14	28
350	2	4	8	16	32
375	2	4	9	18	37
400	3	5	10	21	42
425	3	6	12	24	47
450	3	6	13	26	53
475	4	7	15	29	59
500	4	8	16	33	65
525	4	9	18	36	72
550	5	9	20	39	79
575	5	10	22	43	86
600	6	11	23	47	94
625	6	12	25	51	102
650	7	13	28	55	110

Add reciprocity correction to time in table!

Pinhole exposure compensation time - Table 2

meter setting: f 16

Metered time:	1/8	1/4	1/2	1	2
Aperture	0.125	0.25	0.5	1	2
100	5	10	20	39	78
125	8	15	31	61	122
150	11	22	44	88	176
175	15	30	60	120	239
200	20	39	78	156	313
225	25	49	99	198	396
250	31	61	122	244	488
275	37	74	148	295	591
300	44	88	176	352	703
325	52	103	206	413	825
350	60	120	239	479	957
375	69	137	275	549	1099
400	78	156	313	625	1250
425	88	176	353	706	1411
450	99	198	396	791	1582
475	110	220	441	881	1763
500	122	244	488	977	1953
525	135	269	538	1077	2153
550	148	295	591	1182	2363
575	161	323	646	1292	2583
600	176	352	703	1406	2813
625	191	381	763	1526	3052
650	206	413	825	1650	3301

Add reciprocity correction to time in table!